



DELTA-XERO

THE FUTURE IS SYSTEM RELIABILITY

DX1003-T-PT

The modern, eco-friendly solution to fluid conditioning for Diesel

- Particle filtration down to **0.1 µm**
- Designed for diesel and kerosene
- Smart & effective maintenance system
- Operation and maintenance cost reduction
- Extend equipment lifetime
- Eco-friendly
- Easy to service
- Reduced emissions
- **100% Recycled** media

Maintaining healthy fluid by removing:

- Abrasive material to down 0.1 µm
- Bacteria
- Fungus
- Ashphaltenes
- Wax deposits
- Water bound free and emulsified



DX1003-T-PT

Drive Input	Electric
Connection Ports	1/2" BSP In & 1/2" BSP Out
Flow Indicator	Visual
Suggested System Volume	Fluid dependant
Flow rate	Starting from 6 lpm - Varies per application
Particulate Removal	From 0.1 µm
Weight	30Kg
Dimensions	H 1158mm x D 300 mm x L 550 mm
Material	SS316
DXPT Cartridge QTY	3

© 2022 Delta-Xero All Rights Reserved. All information contained in this publication is indicative only and may be subject to change without prior notice.



Delta-Xero Distribution Ltd
 Unit 5, Pennant Park, Standard Way,
 Fareham, Hampshire,
 PO16 8XU
 t: +44 2392 874 755
 e: sales@delta-xero.com



DELTA-XERO

THE FUTURE IS SYSTEM RELIABILITY

General Arrangement

