



DELTA-XERO

THE FUTURE IS SYSTEM RELIABILITY

DXO Cartridge

The modern, eco-friendly solution to fluid conditioning.

- Particle filtration down to **0.1 μ**
- Designed for mineral and synthetic fluids
- Hydraulic, lube and gear applications
- Smart & effective maintenance system
- Operation and maintenance cost reduction
- Extend equipment lifetime
- Minimised fluid oxidation
- Mitigation and reduction of **varnish**
- Increased production uptime
- Reduced fluid changes
- Eco-friendly
- Easy to service
- Small footprint
- **100% Recycled** media



Maintaining healthy fluid by removing:

- **Bacteria**
- **Water (free and emulsified)**
- **Oxidation products (Sludge and resin)**

Technical Specifications

Part No.	DX10A0001V
Weight (Dry)	1.85 kg
Weight (Saturated)	Up to 4.5 kg
Flow capacity	1 lpm @ 32 cSt
Water absorption, free & bound	Up to 2600 ml
Min and max limits	Min 0°C - Max 100°C
Material	PP Cellulose mix
Package dimensions	192 mm x 192 mm x 265 mm



© 2022 Delta-Xero All Rights Reserved. All information contained in this publication is indicative only and may be subject to change without prior notice.



Delta-Xero Distribution Ltd
Unit E6, Fort Wallington Industrial
Estate, Military Road, Fareham,
Hampshire,
PO16 8XU
t: +44 2392 874 755
e: sales@delta-xero.com